

## KOS-C

## KRUHOVÉ REGULÁTORY VARIABILNÍHO PRŮTOKU VZDUCHU

0...10 V - 0 V =  $V_{\min}$ ; 10 V =  $V_{\max}$



2...10 V - 0 V = closed; 2 V =  $V_{\min}$ ; 10 V =  $V_{\max}$

Provozní režimy:

variabilní průtok, konstantní průtok, otevřeno/zavřeno,  $V_{\min}$ ,  $V_{\max}$ .

Určeno pro rychlosti: 0,5–10 m/s.

Možnost výroby nerezového VAV regulátoru KOS-C.



| Typ   | Rozměry, mm |     |                | Hmotnost kg | V, m³/h |              |
|-------|-------------|-----|----------------|-------------|---------|--------------|
|       | d           | L   | L <sub>i</sub> |             | min     | max          |
| KOS-C | 100         | 390 | 40             | 1,3         | 8       | 34 - 367     |
|       | 125         | 390 | 40             | 1,5         | 13      | 53 - 574     |
|       | 160         | 390 | 40             | 1,8         | 22      | 87 - 940     |
|       | 200         | 390 | 40             | 2,2         | 34      | 136 - 1470   |
|       | 250         | 592 | 40             | 3,5         | 53      | 212 - 2296   |
|       | 315         | 592 | 40             | 4,5         | 84      | 336 - 3645   |
|       | 355         | 600 | 65             | 8,8         | 107     | 427 - 4630   |
|       | 400         | 600 | 65             | 10          | 136     | 543 - 5878   |
|       | 450         | 675 | 65             | 12,3        | 172     | 687 - 7439   |
|       | 500         | 750 | 65             | 15          | 212     | 848 - 9185   |
|       | 560         | 791 | 65             | 20,8        | 266     | 1063 - 11521 |
|       | 630         | 791 | 65             | 27,5        | 336     | 1346 - 14581 |